
# GENERAL-PURPOSE SANS - SMALL-ANGLE NEUTRON SCATTERING DIFFRACTOMETER

The general-purpose SANS diffractometer is optimized for providing information about structure and interactions in materials in the size range of 0.5–200 nm. It will have cold neutron flux on sample and capabilities comparable to those of the best SANS instruments worldwide, including a wide range of neutron wavelengths  $\lambda$ =5–25 Å, resolution  $\delta\lambda/\lambda$ =9-45%, and a 1-m² area detector with 5- × 5-mm² pixel resolution with a maximum counting capability of up to 25 kHz. The sample-to-detector distance can be varied from 1 to 20 m, and the detector can be offset horizontally by up to 45 cm, allowing a total accessible Q range of from <0.001 to 1 Å-¹. The 2-m sample environment area will accommodate large, special-purpose sample environments such as cryomagnets, furnaces, mechanical load frames, and shear cells.



#### APPLICATIONS

- Soft condensed matter: molecular self-assembly and interactions in complex fluids; intermediate order in glassy systems, polymer solutions, gels and blends, colloids, micelles, and microemulsions
- Hard condensed matter: phase separation, grain growth, and orientation in metallurgical alloys, nanocomposites, advanced ceramics, and porous catalytic and adsorbent materials
- Magnetic systems: flux lattices in superconductors, ferrofluids, and the relationship between structural and magnetic domains and ordering

#### FOR MORE INFORMATION, CONTACT

Instrument Scientist: Ken Littrell, littrellkc@ornl.gov, 865.574.4535

Instrument Scientist: Yuri Melnichenko, melnichenkoy@ornl.gov, 865.576.7746

Scientific Associate: Katherine Bailey, baileykm@ornl.gov, 865.574.3989

http://neutrons.ornl.gov/instruments/HFIR/CG2/

## 39

### SPECIFICATIONS

Beam spectrum	λ=4-25 Å Δλ/λ=9-45%
Sample-detec- tor distance	1.1–19.4 m
Detector offset	0–45 cm
Source-sample distance	1.8–17.4 m
Max flux on sample	>2×10 $^7$ n/cm $^2$ /s at $\lambda$ =4.75 Å, $\Delta\lambda$ / $\lambda$ =14%
Detector	commissioning
Detector count rate	commissioning
Momentum Transfer range	$Q = 0.0007 - 1 \text{ Å}^{-1}$ $Q_{\text{max}}/Q_{\text{min}} 10 - 20$

Status: Operational

